


Application of High Resolution Site Characterization Tools for Source Delineation and In-Situ Thermal Treatment Design Optimization

Presented by: Michael Jordan



The Problem

"Most people spend more time and energy going around problems than in trying to solve them." -

Henry Ford (1863 - 1947),

- Remedial Investigations often continue for years or even decades
- Many remedies underperform or fail due to a lack of understanding of site conditions and processes (heterogeneity)
- The cost of failed/ underperforming remedies is large
- The costs of excessive long term monitoring programs related to investigating sites with monitoring wells is large
- The costs of High Resolution Site Characterization, which allows one to avoid failed remedies, is small in comparison, but requires an up front investment to result in lower life cycle costs.

Data Compilation & CSM Development

- Compiled all historic data into a single web hosted database;
- Over 184,000 records were entered
- Worked with our Consultant and Client so that population and access was easily achieved.
- Utilized a collaborative approach in CSM design to compile site knowledge.

Site Data Gap Analysis

- Confirmed limited vertical or horizontal understanding of tar in the subsurface.
- Evaluation of the culvertized stream and former stream bed was incomplete
- Needed to determine impacts to bedrock
- Other source areas not investigated, UST Area, surficial inorganic contamination.

Toolbox for this Site

- Geophysical Clearance and Location Services
- Data Handling and Visualization
- TarGOST w/ Injection logging
- Discrete Soil Coring
- Well Installation
- Onsite and Offsite Analytical Analysis
- Hydrologic Assessments

Tools and Technologies


The Right Tools for the Job



Data Handling and Visualization

- Data stream identification and formatting for rapid use within EVS
- Daily updates allowed stakeholder group to perform work in an adaptive approach.

TarGOST with injection logging



- Completed 54 location
- Approximately 40 feet bgs,
- In ten days

Discrete Soil Coring




- 18 locations completed at co-located with TarGOST
- Analyzed 138 sample intervals for VOCs and SVOCs


- Onsite analytical provide results daily.
- Visual NAPL/Tar interval information logged



Hydrogeologic Assessment

- Completed 21 slug test at 4 existing and 3 newly installed wells.
- Wells to be slug tested were located fully within specific unconsolidated units identified onsite.
- Data was used to confirm special distribution of k indicated by injection logging





EXCELLENCE ON EVERY LEVEL™





Results





Data Compilation and Analysis

- Distributed quantitative data sets were supported by qualitative data
- All data streams were combined into the Site CSM through EVS model
 - Direct sensing (%RE and Ik)
 - Soil analytical results
 - NAPL/Tar observation
 - Soil boring logs
 - Hydrogeologic assessment data

Positive Signal Response




Scatter Response




TarGOST and NAPL/Tar


Distribution




Injection Logging Results (Ik)



Data Compilation





Treatment depths
(not heater depths*)

- 0-10 ft
- 10-20 ft
- 10-30 ft
- 10-35 ft
- 0-35 ft
- 0-45 ft

*Heaters will be 5 ft deeper than the TTZ, casings 7 ft deeper than the TTZ

- ⊗ MPE well to TTZ btm
- ⊗ MPE well to holder btm



Thank you

Michael Jordan
mjordan@cascade-env.com

Follow Cascade on Social



Subscribe to Cascade's email list
www.cascade-env.com